

Works with Tipping Point

- S2600NX
- S5200NX
- S6200NX
- S7100NX
- S7500NX

If your customer requires

- 100% Network Uptime
- Ability to take Tipping Point appliance off-line anytime
 - For maintenance and upgrades
 - Troubleshooting
 - · Replace or reboot anytime
- Configurable bypass TAP breakout, aggregation, regeneration or bypass mode

Traffic Flow - In-Line RESET ACOUND STATUS ACOUND STATUS

Part Numbers:

Chassis

M10G1AC 1U Modular Chassis, Dual AC PSU – Supports 4 TAP Modules M10G1DC 1U Modular Chassis, Dual DC -48vdc PSU – Supports 4 TAP Modules

Breakout, Aggregation, Regeneration/Span, Bypass Modules

M10GMSBP 10Gbps (2) Multi Mode Fiber TAPs / (2) SFP Monitoring Ports
M10GSSBP 10Gbps (2) Single Mode Fiber TAPs (LR) / (2) SFP Monitoring Ports
10Gbps (2) Single Mode Fiber TAPs (ER) / (2) SFP Monitoring Ports
10Gbps (2) Single Mode Fiber TAPs (ER) / (2) SFP Monitoring Ports

SFP+SR10 10Gigabit-SR SFP+ SFP+LR10 10Gigabit-LR SFP+

This Document is for informational purposes only. The information in this document, believed by Garland Technology to be accurate as of the date of publication, is subject to change without notice. Garland Technology assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains. Copyright 2012 Garland Technology LLC. All rights reserved.