

SelectTAP™: Fiber Modular Chassis

1G/10G/25G/40G/100/400G | 1U | TAP 'Breakout' Mode



Network test access points (TAPs) are hardware tools that allow you to access and monitor your network. The passive fiber modular chassis system supports 1Gbps, 10Gbps, 40Gbps, 100Gbps and 400Gbps network speeds.

This high density and high performance monitoring solution accommodates growing data center and enterprise needs for 100G Ethernet networks. The passive fiber modular chassis system features a scalable design allowing you to meet the demands of the network today and tomorrow, while supporting the investment in existing monitoring tools.

Key Features

Chassis supports: 1Gbps, 10Gbps, 25Gbps, 40Gbps, 100Gbps, 400Gbps network speeds

Accommodates 16 to 24 network TAP modules, based on configuration

(24 LC TAP Modules, 16 MPO/MTP® TAP Modules, 16 BiDi LC TAP Modules)

- Durable, all steel construction for chassis and TAP network modules
- Fits into standard 19 inch rack
- No power, no heat, no IP address, no MAC address - 100% passive
- Change network TAP modes on-the-fly or in the future
- Mix and match modules by media and/or speeds
- Supports **single-mode**: OS1/OS2 and **multi-mode**: OM3/OM4/OM5 media for long range and short range environments
- Supports Cisco BiDirectional optical technology
- Supports split ratios of: 90/10, 80/20, 50/50, 70/30, 60/40
- Designed, manufactured and supported in the United States
- Tested and Certified

APPLICATIONS:

- Network & Application Monitoring
- Network & Application Analysis
- Network & Application Performance

+ Breakout Mode is ideal when utilization is very high and packet loss is not an option.

SOLUTIONS:

Passive optical TAPs are ideal for:

- Intrusion Detection Systems
- Application Performance Monitoring
- Lawful Interception
- Network Packet Broker
- Deep Packet Inspection
- Network Analyzer
- Forensics

Competitive Edge

- Supports OS1/ OS2, OM1/OM2 and OM3/OM4/OM5 Media
- New prism based technology reduces bit errors on OM3/OM4/OM5 applications, providing 100% utilization
- Tested and Certified



Have Questions?

sales@garlandtechnology.com
+716.242.8500
garlandtechnology.com

SelectTAP™: Fiber Modular Chassis 1G/10G/25G/40G/100G/400G | 1U Chassis

SelectTAP options							
Model #	Network Speed	Ports	# of TAPs	Split Ratio*	Wavelengths	Media	Connector/Mode
FMC-1U	Fiber Modular Chassis						
OS2501M	1/10/25/40/100G		1	50/50	1290-1330nm 1530-1570nm	Fiber-OS1/OS2	LC Single-Mode Fiber
OS2701M	1/10/25/40/100G		1	70/30	1290-1330nm 1530-1570nm	Fiber-OS1/OS2	LC Single-Mode Fiber
OS2501WM	1/10/25/40/100/400G		1	50/50	1270-1350nm 1510-1590nm	Fiber - OS1/OS2	LC Single Mode Fiber
OS2601WM	1/10/25/40/100/400G		1	60/40	1270-1350nm 1510-1590nm	Fiber - OS1/OS2	LC Single Mode Fiber
OS2701WM	1/10/25/40/100/400G		1	70/30	1270-1350nm 1510-1590nm	Fiber - OS1/OS2	LC Single Mode Fiber
OS2501-PSM4BM	100G			1	50/50	1310nm	Fiber-OS1/OS2
OS2701-PSM4BM	100G	1		70/30	1310nm	Fiber-OS1/OS2	MTP12 B Style Male Connectors (MPO)
OM1501M	1/10G		1	50/50	850-1300nm	Fiber-OM1/OM2	LC Multi-Mode Fiber
OM1701M	1/10G		1	70/30	850-1300nm	Fiber-OM1/OM2	LC Multi-Mode Fiber
OM4501M	1/10/25G		1	50/50	850nm	Fiber-OM3/OM4	LC Multi-Mode Fiber
OM4601M	1/10/25G		1	60/40	850nm	Fiber-OM3/OM4	LC Multi-Mode Fiber
OM4701M	1/10/25G		1	70/30	850nm	Fiber-OM3/OM4	LC Multi-Mode Fiber
OM5501M	1/10/25/40/100G*		1	50/50	850-950nm	Fiber OM5	LC-Multi-Mode
OM5601M	1/10/25/40/100G*		1	60/40	850-950nm	Fiber OM5	LC-Multi-Mode
OM5701M	1/10/25/40/100G*		1	70/30	850-950nm	Fiber OM5	LC-Multi-Mode
OM4501-40GSR4BiDiM	40G			1	50/50	800-950nm	Fiber-OM3/OM4
OM4701-40GSR4BiDiM	40G	1		70/30	800-950nm	Fiber-OM3/OM4	LC Multi-Mode Fiber
OM5501-SR4BiDiM	40/100G*	1		50/50	800-950nm	Fiber OM5	LC Multi-Mode Fiber
OM5701-SR4BiDiM	40/100G*	1		70/30	850-950nm	Fiber OM5	LC Multi-Mode Fiber
OS2502-BiDiM	1G/10G		2	50/50	1270-1350nm 1450-1530nm 1510-1590nm	Fiber-OS2	LC Single-Mode
OS2702-BiDiM	1G/10G		2	50/50	1270-1350nm 1450-1530nm 1510-1590nm	Fiber-OS2	LC Single-Mode
OM4501-SR4BM	40/100G		1	50/50	850nm	Fiber-OM3/OM4	MTP-12 Multi-Mode Fiber
OM4701-SR4BM	40/100G		1	70/30	850nm	Fiber-OM3/OM4	MTP-12 Multi-Mode Fiber
OM5501-SR4BM	40/100/400G*		1	50/50	850-950nm	Fiber OM5	MTP12 Multi-Mode Fiber
OM5601-SR4BM	40/100/400G*		1	60/40	850-950nm	Fiber OM5	MTP12 Multi-Mode Fiber
OM5701-SR4BM	40/100/400G*		1	70/30	850-950nm	Fiber OM5	MTP12 Multi-Mode Fiber
OS23321X3M	1G/10G/25G 40G/100G		1	33.3/ 33.3/ 33.3	1310-1550nm	Fiber-OS2	Fiber LC Single-Mode Fiber
OM43321X3M	1G/10G		1	33.3/ 33.3/ 33.3	850nm	Fiber-OM3/OM4	Fiber LC Multi-Mode Fiber
OM5501-SR8BM	400G		1	50/50	850 nm	Fiber OM5	MPO16 Multi-Mode Fiber
OM5701-SR8BM	400G		1	70/30	850 nm	Fiber OM5	MPO16 Multi-Mode Fiber

OS2 Fiber supports OS1 & OS2; OM1 Fiber supports OM1 & OM2; OM5 Fiber supports OM3 & OM4

Available split ratios: 90/10, 80/20, 50/50, 70/30, 60/40

*100G SWDM4

TAP Chassis – Standard Rack 19"(inch)

Dimensions (WxHxD): 17.40" x 1.75" x 13.45"
(441.96mm x 44.45mm x 341.63mm)



This document is for informational purposes only. The information in this document, believed by Garland Technology to be accurate as of the date of publication, is subject to change without notice. Garland Technology assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains. ©2023 Garland Technology LLC. All Rights Reserved