

# AggregatorTAP: Passive

100M | Portable | Aggregation and Power over Ethernet (PoE)



Network test access points (TAPs) are hardware tools that allow you to access and monitor your network. TAPs are purpose-built hardware devices that let you see every bit, byte and packet.®

AggregatorTAPs are used to capture 100% full duplex traffic that can then be sent to multiple monitoring appliances to analyze your network. This AggregatorTAP supports aggregation and regeneration/SPAN modes, providing flexibility to manage your network.

## Key Features








- Copper network and monitoring ports
- Passive 100M
- Two (2) 1G Aggregated Monitoring ports
- Aggregation-mode only TAP
- Supports Power over Ethernet (PoE)
- Portable, plug and play design
- Easy configuration; switches on back
- Supports jumbo frames and passes physical errors
- Single external power supply
- 100% secure and invisible; no IP address, no MAC address; cannot be hacked
- Tested and Certified

### APPLICATIONS:

- TAP once and send to multiple monitoring devices.
- Capture full duplex traffic from both directions.

### SOLUTIONS:

AggregatorTAPs are ideal for:

-  Wireshark
-  Analyzers
-  Intrusion Detection System
-  Application Performance Monitoring
-  Lawful Intercept
-  Packet Capture
-  Data Forensics

### Competitive Edge

- Completely passive
- Portable, Plug & Play
- Tested and Certified



### Have Questions?

sales@garlandtechnology.com  
+716.242.8500  
garlandtechnology.com

# AggregatorTAP: Passive

100M | Portable | Aggregation and Power over Ethernet (PoE)

Model #	Network Speed	Media		Modes			
		Network	Monitor	Breakout	Aggregation	Regeneration	Bypass
RMP-1U				1U Rack Mount Kit - Holds up to 4 Portable TAPs			
P100CCA	100M	2 Copper RJ-45	2 Copper 1000M RJ-45	No	Yes	Yes	No

## Additional Specifications

### Dimensions (HxWxD):

1.15" x 3.9" x 3.84"

(29.21mm x 99.06mm x 97.6mm)

**Weight:** 0.45 lbs (0.204 kg)

**Ambient Temperature:** 0C to +40C / +32F to +104F

**Storage Temperature:** -20C to +70C / -4F to +158F

**Voltage:** 5VDC

**Current (nominal):** 0.36 Amps

**Maximum consumption:** 1.8 Watts

**Humidity:** 90% non-condensing

## Network Flow

