

Copper Aggregator Network TAPs

10/100/1000M (1G) | Portable | Supports TAP "Breakout," Aggregation, Regeneration/SPAN modes




Network test access points (TAPs) are hardware tools that allow you to access and monitor your network. Aggregating TAPs are used to capture 100% full duplex traffic; the traffic can then be sent to multiple monitor appliances to analyze your network. Aggregating TAPs are purpose-built hardware devices that let you see every bit, byte and packet.®

Support breakout, aggregation and regeneration/SPAN modes providing flexibility to manage your network.

Key Features

- Portable, Plug & Play
- Easy configuration; switches on back
- Listen-only TAP for out-of-band monitoring
- Supports breakout, aggregation, regeneration/SPAN modes
- Supports Link Speed Synchronization
- Supports jumbo frames
- Passes physical errors
- 1U rack mount holds up to four portable TAPs
- 100% secure and invisible; no IP address, no MAC address; cannot be hacked
- Made, tested and certified in USA

Network Flow



APPLICATIONS:

- Out-of-band monitoring
- Aggregate one to multiple monitoring devices.
- Capture full duplex traffic from both directions.
- Switch to breakout mode for full utilization to capture 100% traffic.

SOLUTIONS:

Aggregator TAPs are ideal for:



Competitive Edge

- Supports Link Speed Synchronization.
- Portable, Plug & Play Design
- Design supports breakout, aggregation, regeneration/SPAN modes.
- Tested and Certified.




Have Questions?

sales@garlandtechnology.com
+716.242.8500
garlandtechnology.com

Copper Aggregator Network TAPs

10/100/1000M (1G) | Portable | Supports TAP "Breakout," Aggregation, Regeneration/SPAN modes

Model #	Network Speed	Media		Modes			
		Network	Monitor	Breakout	Aggregation	Regeneration	Bypass
RMP-1U		1U Rack Mount Kit - Holds up to 4 Portable TAPs					
P1GCCAS	10/100/1000M	2 Copper RJ-45	2 Copper RJ-45	Yes	Yes	Yes	No
P1GCSAS	10/100/1000M	2 Copper RJ-45	2 SFP	Yes	Yes	Yes	No

Additional Specifications

Voltage: 90 -264VAC

Current: 1.77 Amps

Max. Consumption: 8.85 Watts

Ambient Temp.: 0C to +40C / +32F to +104F

Operating Re. Humidity: 90% non-condensing


Dimensions (HxWxD):

1.15" x 3.9" x 6.5"

(29.21mm x 99.06mm x 165.10mm)

Weight: 0.7lbs (0.317kg)

Use Case



Fail-safe

Garland Technology's Fail-Safe feature allows Copper TAP's to fail-to-wire in the event of power loss. This ensures the TAP will never disrupt the flow of network traffic.



This document is for informational purposes only. The information in this document, believed by Garland Technology to be accurate as of the date of publication, is subject to change without notice. Garland Technology assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains. ©2018 Garland Technology LLC. All Rights Reserved